

A UNITED STATES
DEPARTMENT OF
COMMERCE
PUBLICATION

NBS TECHNICAL NOTE 387



U. S.
DEPARTMENT
OF
COMMERCE

National
Bureau
of Standards

Hydrogen Spin Exchange Frequency Shifts

NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards¹ was established by an act of Congress March 3, 1901. Today, in addition to serving as the Nation's central measurement laboratory, the Bureau is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. To this end the Bureau conducts research and provides central national services in four broad program areas. These are: (1) basic measurements and standards, (2) materials measurements and standards, (3) technological measurements and standards, and (4) transfer of technology.

The Bureau comprises the Institute for Basic Standards, the Institute for Materials Research, the Institute for Applied Technology, the Center for Radiation Research, the Center for Computer Sciences and Technology, and the Office for Information Programs.

THE INSTITUTE FOR BASIC STANDARDS provides the central basis within the United States of a complete and consistent system of physical measurement; coordinates that system with measurement systems of other nations; and furnishes essential services leading to accurate and uniform physical measurements throughout the Nation's scientific community, industry, and commerce. The Institute consists of an Office of Measurement Services and the following technical divisions:

Applied Mathematics—Electricity—Metrology—Mechanics—Heat—Atomic and Molecular Physics—Radio Physics²—Radio Engineering²—Time and Frequency²—Astrophysics²—Cryogenics.²

THE INSTITUTE FOR MATERIALS RESEARCH conducts materials research leading to improved methods of measurement standards, and data on the properties of well-characterized materials needed by industry, commerce, educational institutions, and Government; develops, produces, and distributes standard reference materials; relates the physical and chemical properties of materials to their behavior and their interaction with their environments; and provides advisory and research services to other Government agencies. The Institute consists of an Office of Standard Reference Materials and the following divisions:

Analytical Chemistry—Polymers—Metallurgy—Inorganic Materials—Physical Chemistry.

THE INSTITUTE FOR APPLIED TECHNOLOGY provides technical services to promote the use of available technology and to facilitate technological innovation in industry and Government; cooperates with public and private organizations in the development of technological standards, and test methodologies; and provides advisory and research services for Federal, state, and local government agencies. The Institute consists of the following technical divisions and offices:

Engineering Standards—Weights and Measures—Invention and Innovation—Vehicle Systems Research—Product Evaluation—Building Research—Instrument Shops—Measurement Engineering—Electronic Technology—Technical Analysis.

THE CENTER FOR RADIATION RESEARCH engages in research, measurement, and application of radiation to the solution of Bureau mission problems and the problems of other agencies and institutions. The Center consists of the following divisions:

Reactor Radiation—Linac Radiation—Nuclear Radiation—Applied Radiation.

THE CENTER FOR COMPUTER SCIENCES AND TECHNOLOGY conducts research and provides technical services designed to aid Government agencies in the selection, acquisition, and effective use of automatic data processing equipment; and serves as the principal focus for the development of Federal standards for automatic data processing equipment, techniques, and computer languages. The Center consists of the following offices and divisions:

Information Processing Standards—Computer Information—Computer Services—Systems Development—Information Processing Technology.

THE OFFICE FOR INFORMATION PROGRAMS promotes optimum dissemination and accessibility of scientific information generated within NBS and other agencies of the Federal government; promotes the development of the National Standard Reference Data System and a system of information analysis centers dealing with the broader aspects of the National Measurement System, and provides appropriate services to ensure that the NBS staff has optimum accessibility to the scientific information of the world. The Office consists of the following organizational units:

Office of Standard Reference Data—Clearinghouse for Federal Scientific and Technical Information³—Office of Technical Information and Publications—Library—Office of Public Information—Office of International Relations.

¹ Headquarters and Laboratories at Gaithersburg, Maryland, unless otherwise noted; mailing address Washington, D.C. 20234.

² Located at Boulder, Colorado 80302.

³ Located at 5285 Port Royal Road, Springfield, Virginia 22151.

UNITED STATES DEPARTMENT OF COMMERCE
Maurice H. Stans, Secretary
NATIONAL BUREAU OF STANDARDS • Lewis M. Branscomb, Director



TECHNICAL NOTE 387

ISSUED MARCH 1970

Nat. Bur. Stand. (U.S.), Tech. Note 387, 13 pages (March 1970)
CODEN: NBTNA

Hydrogen Spin Exchange Frequency Shifts

Helmut Hellwig

Atomic Frequency and Time Standards Section
Time and Frequency Division
Institute for Basic Standards
National Bureau of Standards
Boulder, Colorado 80302



NBS Technical Notes are designed to supplement the Bureau's regular publications program. They provide a means for making available scientific data that are of transient or limited interest. Technical Notes may be listed or referred to in the open literature.

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	1
1. INTRODUCTION	1
2. SPIN EXCHANGE FREQUENCY SHIFT	2
3. CONDITIONS FOR THE HYDROGEN STORAGE BEAM TUBE	3
4. CONDITIONS FOR THE HYDROGEN MASER OSCILLATOR	6
5. TUNING OF THE HYDROGEN MASER	9
6. CONCLUSIONS	11
7. REFERENCES	13

HYDROGEN SPIN EXCHANGE FREQUENCY SHIFTS

Helmut Hellwig

Frequency shifts due to hydrogen spin exchange collisions are discussed for the hydrogen maser and the hydrogen storage beam tube. The combined effects of spin exchange and cavity pulling in the hydrogen maser are evaluated with emphasis on frequency errors introduced by standard tuning procedures. It is found that an automatic cavity tuning system based on a variation of the linewidth does not introduce a frequency error. In contrast, manual tuning procedures based on an interpolation of measurements at different cavity settings do not yield a perfect compensation of spin exchange effects. However, the frequency error becomes only significant at unnecessarily large cavity offsets.

The smallness of the spin exchange shifts and the near absence of cavity pulling in a hydrogen storage beam tube are expected to permit a determination of spin exchange shifts by varying the beam intensity with a precision adequate for stability and accuracy figures of 10^{-14} or better.

Key Words: Frequency pulling; hydrogen beam tube; hydrogen maser; maser tuning; spin exchange.

1. INTRODUCTION

Collisions between radiating hydrogen atoms cause a broadening of the resonance line as well as a frequency shift. An important feature of the hydrogen maser is the automatic cancellation of the spin exchange frequency shift by cavity pulling if the hydrogen maser tuning method is based on varying the hydrogen relaxation time. The most widely used method is the beam intensity modulation technique (Vanier and Vessot, 1964).

A need was felt to discuss and recheck this result. An additional impetus for reevaluating this aspect of the hydrogen maser was provided by the fact that only one short discussion of spin exchange and cavity pulling is published in the open literature (Crampton, 1967) although the result is widely used in experiments with the hydrogen maser (Vanier and Vessot, 1964).¹ Furthermore, a quantitative estimate of the spin exchange frequency shift to be expected in the proposed hydrogen storage beam tube was needed (Hellwig, 1970).

The following discussion starts from basic equations for spin exchange effects given by Bender (1963). The treatment differs somewhat from the one given by Crampton (1967); in particular a detailed discussion of the cavity pulling in combination with spin exchange shifts is given, and the frequency errors associated with maser tuning techniques are evaluated.

2. SPIN EXCHANGE FREQUENCY SHIFT

The shifted frequency² ω' differs from the unperturbed transition frequency ω_0 by an amount proportional to the rate of spin exchange phase shifting V and to the population difference $(\rho_{22} - \rho_{44})$ of the two $m_F = 0$ levels. The relationships are given by (19), (22), and (24) in Bender's article (1963)

$$\omega' - \omega_0 = -\frac{1}{4} V (\rho_{22} - \rho_{44}) \quad (1)$$

$$V = 2\pi n \bar{v}_{rel} \int_0^{\infty} \{\sin \Delta(R)\} R dR \quad (2)$$

¹ Every publication giving a frequency determination of the hydrogen maser relies on the automatic cancellation of the spin exchange shift by cavity pulling when the maser is tuned.

² Throughout this paper ω is just called "frequency" although, in a strict sense, it is the angular frequency.

$$\rho_{22} - \rho_{44} = \frac{K^2 + (\omega - \omega')^2}{[K^2 + (\omega - \omega')^2] [2 + U/r] + \frac{8\beta^2 K}{r}} \quad (3)$$

The symbols have the following meaning: ω = running frequency; n = atomic density; \bar{v}_{rel} = relative atomic velocity; R = collision parameter; $\Delta(R)$ = phase shift; K = total relaxation constant; U = rate of spin exchange collisions; β = rf magnetic field parameter; r = rate of escape of atoms from the bulb. K and β can be expressed as

$$K = r + \frac{1}{4} U \quad (4)$$

$$\beta = \frac{\mu_0 \langle H_z \rangle_b}{2 \hbar} \quad (5)$$

where μ_0 = magnetic dipole moment of the transition, and $\langle H_z \rangle_b$ = average magnetic rf field in the bulb region. It must be noted that relaxation processes other than escape from the bulb and spin exchange are not included in this discussion.

3. CONDITIONS FOR THE HYDROGEN STORAGE BEAM TUBE

The hydrogen storage beam tube (Hellwig, 1970) is a proposed new device which potentially combines the advantages of the hydrogen maser with those of a beam tube. Its concept is a logical extension of Ramsey's original storage beam proposal and his "bounce box" experiments with cesium (Kleppner, Ramsey, and Fjelstad, 1956) which led to the development of the hydrogen maser (Kleppner, Goldenberg, and Ramsey, 1962).

The hydrogen storage beam tube resembles essentially the configuration of a hydrogen maser, however it is operated well below oscillation threshold, and an external microwave signal is injected into the cavity. The number of atoms leaving the bulb which have undergone a transition is monitored with a second selector magnet and a beam detector in a fashion quite similar to the standard operational principle of an atomic beam tube.

Of the various aspects of the hydrogen storage beam tube the one which is of importance to the discussion presented here is the near absence of cavity pulling. For passive beam tube devices one obtains approximately a pulling which is proportional to the ratio of the linewidths of cavity and atomic transition squared (Holloway and Lacey, 1964) whereas the pulling in a maser is directly proportional to this ratio as can be seen from (20) below. As a result the cavity pulling in the hydrogen storage beam tube can be expected to be reduced by many orders of magnitude as compared to the hydrogen maser (Hellwig, 1970).

In the following we shall estimate the spin exchange frequency shift to be expected in a hydrogen storage beam tube.

We assume that beam intensities of 10^{12} atoms per second at storage times of about 1 s shall not be exceeded.³ For these conditions the spin exchange line broadening is small compared to the linewidth due to the storage time. We therefore may use the approximations

$$U/r \ll 1 \text{ and } K \approx r .$$

³ For a bulb of 10^3 cm^3 volume this corresponds to an atomic density of about 10^9 atoms per cm^3 .

We furthermore restrict ourselves to microwave driving frequencies well within the linewidth $\delta \omega = 2K$ of the transition. We may then use the approximation

$$\omega - \omega' \ll K.$$

With the above approximations (3) simplifies to

$$\rho_{22} - \rho_{44} \approx \frac{r^2}{2r^2 + 8\beta^2} = \frac{1}{2 + 8(\beta/r)^2}. \quad (6)$$

The power of the exciting microwave signal will approximately be chosen as

$$\frac{\beta}{r} = \frac{\pi}{2}. \quad (7)$$

Bender (1963) evaluated numerically the integral in (2), and gave as a result

$$V \approx 13\pi a_0^2 n \bar{v}_{\text{rel}} \quad (8)$$

where a_0 is the Bohr radius ($a_0 = 0.529 \times 10^{-8}$ cm). After combining (1), (6), (7), and (8) we obtain with $\bar{v}_{\text{rel}} = 2 \times 10^5$ cm/s

$$\omega' - \omega_0 = kn \quad (9)$$

where $k \approx -2.6 \times 10^{-12}$ cm³/s, and n is measured in cm⁻³.

The spin exchange frequency shift is proportional to the atomic density n , and its value for the assumed highest density of $n = 10^9$ atoms/cm³ is $\omega' - \omega_0 \approx -2.6 \times 10^{-3} \text{ s}^{-1}$ or a fractional frequency shift of about 3×10^{-13} . According to (9) this frequency shift is linear with the atomic density and can therefore be measured conveniently by varying the beam intensity. It has to be noted that a variation of the beam intensity causes only negligible cavity pulling due to the near-absence of this effect in the beam tube device as was pointed out previously.

4. CONDITIONS FOR THE HYDROGEN MASER OSCILLATOR

The condition for self-sustained maser oscillations can be written as

$$P_{\text{rad}} = P_{\text{abs}} \quad (10)$$

where the radiated power is given by

$$P_{\text{rad}} = n V_b \hbar \omega \frac{d\rho_{22}}{dt} \quad (11)$$

and the absorbed power by

$$P_{\text{abs}} = \frac{\omega}{Q} \frac{V_c}{8\pi} \langle H^2 \rangle_c \quad (12)$$

V_b is the bulb volume, V_c the cavity volume, $d\rho_{22}/dt$ the rate of emission from one atom, and $\langle H^2 \rangle$ the average squared rf magnetic field in the cavity. The rate of emission was given by Bender (1963) as

$$\frac{d\rho_{22}}{dt} = \frac{2\beta^2 K}{[K^2 + (\omega - \omega')^2][2 + U/r] + \frac{8\beta^2 K}{r}} . \quad (13)$$

The combination of (10) to (13) yields

$$[K^2 + (\omega - \omega')^2][2 + U/r] + \frac{8\beta^2 K}{r} = \frac{16\pi \hbar Q V_b \beta^2}{V_c \langle H^2 \rangle_c} nK . \quad (14)$$

β^2 in (14) can be substituted from (5). The filling factor η' as defined by Kleppner and Vessot et al. (1965) is given by

$$\eta' = \frac{\langle H_z \rangle_b^2 V_b}{\langle H^2 \rangle_c V_c} . \quad (15)$$

We introduce the parameter λ' which contains only constants for a given maser configuration

$$\lambda' = \frac{\hbar}{16\pi \mu_0^2 \eta' Q} . \quad (16)$$

Equations (14) to (16) combine with (1), (3), and (5) to

$$\omega' - \omega_0 = -\lambda' \frac{V}{n} \left[1 + \left(\frac{\omega - \omega'}{K} \right)^2 \right] K . \quad (17)$$

Inserting (8) into (17) leads to

$$\omega' - \omega_0 = -13\pi a_0^2 \bar{v}_{\text{rel}} \lambda' \left[1 + \left(\frac{\omega - \omega'}{K} \right)^2 \right] K. \quad (18)$$

If we restrict the frequencies to a small range around ω' we obtain with $C = 13\pi a_0^2 \bar{v}_{\text{rel}} \lambda'$

$$\omega' - \omega_0 = -CK. \quad (19)$$

Equations (17) and (18) do not contain explicitly the beam intensity; instead, the spin exchange frequency shift is proportional to the total linewidth $\delta\omega_a = 2K$. At first the result (19) is surprising because one would expect $(\omega' - \omega_0) \rightarrow 0$ for $\delta\omega_a \rightarrow \delta\omega_E$ where $\delta\omega_E$ is the linewidth due to escape from the bulb alone (vanishing contribution of spin exchange effects). However, (18) does not permit the limit of vanishing spin exchange effects. The equation was derived using the condition (10) for self-sustained maser oscillations and is therefore only valid under these conditions. In order to realize an oscillating maser in the limit $\delta\omega_a \rightarrow \delta\omega_E$, the parameter⁴ λ' has to approach zero, and $(\omega' - \omega_0) \rightarrow 0$ according to (18).

⁴ λ' relates to the maser oscillation parameter q , which was defined by Kleppner and Vessot et al. (1965).

5. TUNING OF THE HYDROGEN MASER

The pulling of the maser output frequency by a cavity which is detuned from the atomic transition frequency is one of the earliest discoveries in maser theory (Gordon, Zeiger, and Townes, 1955), and is quantitatively given by (Shirley, 1968)

$$\omega' = \frac{\delta \omega_c \omega_a + \delta \omega_a \omega_c}{\delta \omega_c + \delta \omega_a} \quad (20)$$

where $\delta \omega_c$ and $\delta \omega_a$ are the linewidths of cavity and transition line, respectively, and ω_a is the atomic transition frequency. Spin exchange is included by substituting ω' for ω_a . We also substitute (Q = loaded cavity Q)

$$\delta \omega_c = \frac{\omega_c}{Q} \text{ and } \delta \omega_a = 2K$$

and obtain

$$\omega - \omega' = \frac{K}{(\omega_c/2Q) + K} (\omega_c - \omega') . \quad (21)$$

ω' can be expressed from (18), and (21) then reads after some simple regrouping

$$\omega - \omega_0 = \frac{K}{(\omega_c/2Q) + K} \left[\omega_c - \omega_0 - \frac{\omega_c}{2Q} C \left(\frac{\omega - \omega'}{K} \right)^2 \right] . \quad (22)$$

If we use the approximations

$$\frac{\omega_c}{2Q} \gg K \text{ and } \omega - \omega' \ll K$$

(22) simplifies to

$$\omega - \omega_0 = \frac{2Q}{\omega_c} K \left(\omega_c - \omega_0 - \frac{\omega_c}{2Q} C \right). \quad (23)$$

Equation (23) is the standard "tuning equation" for the hydrogen maser (Vanier and Vessot, 1964). If the maser is tuned so that a variation of K does not cause a change in the maser output frequency then the maser frequency is equal to the unperturbed atomic transition frequency ($\omega = \omega_0$), and the cavity is detuned by an amount equal to the spin exchange frequency shift ($\omega_c - \omega_0 = C \omega_c / 2Q$) as can be seen from (23).

The error committed in tuning the maser in this fashion can be evaluated from the above approximations. Omitting K in the denominator of the "pulling factor" in (22) does not introduce any error in the tuning procedure. The omission of the last, K -dependent, term in (22) seems to introduce a frequency error. The K -dependent part of this term can be rewritten using (19)

$$\left(\frac{\omega - \omega'}{K} \right)^2 = \left(\frac{\omega - \omega_0 + CK}{K} \right)^2 = \left(\frac{\omega - \omega_0}{K} + C \right)^2. \quad (24)$$

The constant C in this expression does not introduce an error in the above tuning method. The K -dependent part $(\omega - \omega_0)/K$ approaches zero as the maser is tuned ($\omega \rightarrow \omega_0$). As a result no appreciable frequency error is introduced by a tuning procedure which uses the variation of K .

This is only true for experiments where the maser is actually set to oscillate on the transition frequency ω_0 as for example in automatic servo tuning systems (Hellwig and Pannaci, 1967; and Vessot, Levine, Mueller, and Baker, 1967). Frequently, however, the maser frequency is only indirectly determined using two or more cavity settings at which K is varied (Vanier and Vessot, 1964). The maser frequency is then calculated using a linear interpolation between the measured variations of the maser output frequency. In this case a frequency error is introduced which corresponds to the variation with K of the last term in (22). This term can be written as $-C \frac{(\omega - \omega')^2}{K}$. The error follows then approximately as $C \frac{(\omega - \omega')^2}{K^2} \Delta K$, where ΔK is the variation of K . The maser constant C has typically a value of $C \approx 10^{-2}$. Fortunately, the error has an appreciable magnitude only if fairly large cavity offsets and large K -variations are used. For example a cavity setting corresponding to a fractional maser frequency offset of 10^{-10} will produce a fractional error of about 10^{-13} if $\Delta K \approx K \approx 1 \text{ s}^{-1}$.

6. CONCLUSIONS

The discussion given in this report indicates that an automatic cavity servo control based on varying the linewidth of the atomic transition yields an exact tuning of the maser. The spin exchange frequency shift will be perfectly compensated by a proper cavity detuning. A manual tuning procedure in which the maser tuning is found by interpolating between measurements at different cavity settings will introduce in general a systematic error due to an incomplete compensation of frequency shifts. However, this error only has an appreciable magnitude if unnecessarily large cavity offsets are used.

It was pointed out that the automatic compensation of spin exchange and cavity pulling effects, as described by (23), is only valid for an oscillating maser.

In a passive device such as the proposed hydrogen storage beam tube the frequency shift due to spin exchange is present. The shift is linear with the beam intensity (atomic density in the storage bulb) and can be measured and corrected for by varying the beam flux. The magnitude of the shift is small; of the order of 10^{-13} for typical beam intensities and storage times. Thus only a moderate measurement precision and a moderate control of the beam flux is necessary if stabilities and accuracies of 10^{-14} are the design goal of a passive device (Hellwig, 1970).

7. REFERENCES

- Bender, P. L. (1963), Effects of hydrogen-hydrogen exchange collisions, *Phys. Rev.* 132, 2154-2158.
- Crampton, S. B. (1967), Spin-Exchange shifts in the hydrogen maser, *Phys. Rev.* 158, 57-61.
- Gordon, J. P., H. J. Zeiger, and C. H. Townes (1955), The maser—new type of microwave amplifier, frequency standard, and spectrometer, *Phys. Rev.* 99, 1264-1274.
- Hellwig, H. (1970), the hydrogen storage beam tube, a proposal for a new frequency standard. Accepted for publication in *Metrologia* 6, No. 2, April 1970.
- Hellwig, H., and E. Pannaci (1967), Automatic tuning of hydrogen masers, *Proc. IEEE*, 55, 551-552.
- Holloway, J. H., and R. F. Lacey (1964), Factors which limit the accuracy of cesium atomic beam frequency standards, *Proc. CIC, Lausanne*, 317-331.
- Kleppner, D., H. C. Berg, S. B. Crampton, N. F. Ramsey, R. F. C. Vessot, H. E. Peters, and J. Vanier (1965), Hydrogen-maser principles and techniques, *Phys. Rev.* 138, A972-A983.
- Kleppner, D., H. M. Goldenberg, and N. F. Ramsey (1962), Theory of the hydrogen maser, *Phys. Rev.* 126, 603-615.
- Kleppner, D., N. F. Ramsey, and P. Fjelstad (1958), Broken atomic beam resonance experiment, *Phys. Rev. Letters* 1, 232-233.
- Shirley, J. H. (1968), Dynamics of a simple maser model, *American J. Phys.* 36, 949-963.
- Vanier, J., and R. F. C. Vessot (1964), Cavity tuning and pressure dependence of frequency in the hydrogen maser, *Appl. Phys. Letters* 4, 122-123.
- Vessot, R. F. C., M. Levine, L. Mueller, and M. Baker (1967), The design of an atomic hydrogen maser system for satellite experiments, *Proc. 21st Annual Symposium on Frequency Control, Fort Monmouth, N. J.*, 512-542.

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH reports National Bureau of Standards research and development in physics, mathematics, chemistry, and engineering. Comprehensive scientific papers give complete details of the work, including laboratory data, experimental procedures, and theoretical and mathematical analyses. Illustrated with photographs, drawings, and charts.

Published in three sections, available separately:

● Physics and Chemistry

Papers of interest primarily to scientists working in these fields. This section covers a broad range of physical and chemical research, with major emphasis on standards of physical measurement, fundamental constants, and properties of matter. Issued six times a year. Annual subscription: Domestic, \$9.50; foreign, \$11.75*.

● Mathematical Sciences

Studies and compilations designed mainly for the mathematician and theoretical physicist. Topics in mathematical statistics, theory of experiment design, numerical analysis, theoretical physics and chemistry, logical design and programming of computers and computer systems. Short numerical tables. Issued quarterly. Annual subscription: Domestic, \$5.00; foreign, \$6.25*.

● Engineering and Instrumentation

Reporting results of interest chiefly to the engineer and the applied scientist. This section includes many of the new developments in instrumentation resulting from the Bureau's work in physical measurement, data processing, and development of test methods. It will also cover some of the work in acoustics, applied mechanics, building research, and cryogenic engineering. Issued quarterly. Annual subscription: Domestic, \$5.00; foreign, \$6.25*.

TECHNICAL NEWS BULLETIN

The best single source of information concerning the Bureau's research, developmental, cooperative and publication activities, this monthly publication is designed for the industry-oriented individual whose daily work involves intimate contact with science and technology—for engineers, chemists, physicists, research managers, product-development managers, and company executives. Annual subscription: Domestic, \$3.00; foreign, \$4.00*.

* Difference in price is due to extra cost of foreign mailing.

Order NBS publications from:

Superintendent of Documents
Government Printing Office
Washington, D.C. 20402

NONPERIODICALS

Applied Mathematics Series. Mathematical tables, manuals, and studies.

Building Science Series. Research results, test methods, and performance criteria of building materials, components, systems, and structures.

Handbooks. Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications. Proceedings of NBS conferences, bibliographies, annual reports, wall charts, pamphlets, etc.

Monographs. Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

National Standard Reference Data Series. NSRDS provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated.

Product Standards. Provide requirements for sizes, types, quality and methods for testing various industrial products. These standards are developed cooperatively with interested Government and industry groups and provide the basis for common understanding of product characteristics for both buyers and sellers. Their use is voluntary.

Technical Notes. This series consists of communications and reports (covering both other agency and NBS-sponsored work) of limited or transitory interest.

Federal Information Processing Standards Publications. This series is the official publication within the Federal Government for information on standards adopted and promulgated under the Public Law 89-306, and Bureau of the Budget Circular A-86 entitled, Standardization of Data Elements and Codes in Data Systems.

CLEARINGHOUSE

The Clearinghouse for Federal Scientific and Technical Information, operated by NBS, supplies unclassified information related to Government-generated science and technology in defense, space, atomic energy, and other national programs. For further information on Clearinghouse services, write:

Clearinghouse
U.S. Department of Commerce
Springfield, Virginia 22151